



Water Tight Technologies, LLC  
P.O. Box 899  
Payson, AZ 85547  
www.britenez.com

## Product Data Sheet

### **TPO Walkway Pad Roll** (Heat Welded)

#### **Description:**

*BRITE-n-EZ™ Walkway Pad Roll* is an extruded and embossed TPO product. This product is heat welded to TPO membrane or installed with seam tape and used where there is high traffic areas on the roof top.

#### **Physical Properties:**

PROPERTY	PHYSICAL PROPERTIES
Color	White
Specific Gravity	1.43
Cure State	Cured
Weight	118 lb / roll

#### **Installation:**

The application of *BRITE-n-EZ™ Walkway Pad Rolls* should be as follows:

1. Be sure membrane surface is clean and dry.
2. Heat weld in place directly to TPO membrane surface or
3. Attached *Walkway Pad Roll* to TPO membrane with seam tape on all edges, per the installation directions for *BRITE-n-EZ™ Seam Tape*.

#### **Product Data:**

**Roll Size:** 1/8" thick (125 mil) x 30" x 50'

**Carton Size:** 1 roll each

**Storage:** Store *BRITE-n-EZ™ Walkway Pad Rolls* away from sources of punctures and physical damage, in original shipping package. Store indoors in a cool dry and well ventilated facility.