

Water Tight Technologies, LLC P.O. Box 899 Payson, AZ 85547 www.britenez.com

Description:

BRITE-n-EZ™ TPO Outside Corner with Tape is used to flash outside corners. This is a pre-molded corner that is 6" by 6" with a sticky back. BRITE-n-EZ™ TPO Outside Corner is offered as a convenience to the contractor. Because most corners are not exactly 90 degrees, in most instances, it is more advantageous to use BRITE-n-EZ™ Uncured Black Flashing With Tape to insure the water tight integrity of the corner flashing detail.

.Physical Properties:

PROPERTY	PHYSICAL PROPERTIES
Color	White solid membrane with tacky white solid backing
Solids	99+%
Specific Gravity	0.80 - 0.97
Hazardous Components	Minimal amounts of Calcium Carbonate and Titanium Dioxide in an encapsulated form.
Flash Point	> 200°C for adhesive
% Volatiles	0.7% maximum in adhesive backing
Weight	2.0 lbs +/- 0.5lbs

Installation:

- Membrane and substrate to which corner will be applied must be clean, dry and free of foreign materials such as grease, oil, debris and other materials which could inhibit adhesion.
- BRITE-n-EZ™ Tape Primer should be applied to all surfaces prior to adhering the corner with a BRITE-n-EZ™ Scrub Pad.
- Peel backing paper from vertical portion of corner. Spread corner so that the center is contacted first and then press toward outside of corner, working away from the center.

Product Data Sheet

Outside Corners W/Tape

- 4. Reach under deck portion of outside corner, remove backing paper at 45° angle working from center.
- 5. Roll entire corner with steel hand roller.

Product Data:

Available Sizes: 6" x 6"

Carton Sizes: 8 per carton

Storage: Store in cool, dry, well ventilated facility with temperatures not to exceed 130°F.

Shelf Life: ROTATE STOCK. Although this product should not deteriorate, good inventory practices of stock rotation should still be utilized.

Precautionary Data:

To avoid sources of punctures and physical damage, take care when moving, transporting or handling.