

PRODUCT DATA SHEET
**ROUND FASTENING
PLATES – 3”**



Water Tight Technologies, LLC
P.O. Box 899, Payson, AZ 85547
www.watertighttech.com

DESCRIPTION:

RUBBERALL® 3” Round Plates are designed to distribute clamping force of commercial roofing fasteners. Popular for insulation board and coverboard attachment to steel, wood or masonry roof deck to prepare an approved base for the application of Rubberall® membrane. Proper installation is important to prevent wind up-lift.

APPLICATION: Approved insulation boards must be secured by screws and plates in the patterns as outlined in the Rubberall® Installation Manual. Coverage should be one screw and plate every two sq. ft. for insulation board around the perimeter of the roof and one screw and plate every four sq. ft. for the remainder of the roof deck.

TYPICAL PHYSICAL PROPERTIES:

Material:	AZ55 Galvalume Steel
Diameter:	3” (76 mm)
Thickness:	.019” 25 ga
Material Spec:	SAE J1392

FEATURES:

- Multiple rib design for strength
- Recessed fastener hole for low installed profile.
- Center hole sized to fit #12, #14 and #15 fasteners

STORAGE:

Packaged in re-sealable plastic pails. 1,000 plates per pail. Store in area protected from weather.

Updated 2/20/2023