




Water Tight Technologies, LLC
P.O. Box 899, Payson, AZ 85547



SECTION 1 – PRODUCT IDENTIFICATION

Product Name: TPO Wall Flashings (Self Adhered)	Manufacturer's Name: Water Tight Technologies, LLC
Item Number(s): TWFA2050	Manufacturer's Address: P.O. Box 899, Payson, AZ 85547
24 Hour Emergency Telephone Number: CHEMTREC – United States 800-424-9300 ; International 202-483-7616 (collect)	NFPA Acute Hazard Rating: Health 0, Flammability 0, Reactivity 0 HMIS Acute Hazard Rating: Health 0, Flammability 0, Reactivity 0
Chemical Name/Synonyms: N/A	Chemical Family: Mixture

SECTION 2 – CHEMICAL COMPOSITION

Ingredient Components (chemical names) Hazardous Components 1% or greater; Carcinogens 0.1% or greater:	% wt or % vol	Case No.	% wt or % vol	OSHA STEL	OSHA PEL ACGIH	ACGIH TLV
Non-Hazardous Ingredients	100					
Total	100					


There are no recognized hazards associated with normal use of this product.

SECTION 3 – PHYSICAL & CHEMICAL CHARACTERISTICS

Appearance/Odor: Solid with no odor. White color is stock item but gray and tan can be special ordered.	Physical State: Solid	Solubility in Water: Insoluble
Boiling Point: N/A	Specific Gravity (HO=1) 0.90 – .96	Melting Point: 350° F – membrane; 270° F Adhesive
Vapor Pressure: N/A	Additional Information: N/A	Freezing Point: N/A
Percent Volatiles: N/A	Reactivity in Water: None	



Water Tight Technologies, LLC
 P.O. Box 899, Payson, AZ 85547



SECTION 4- FIRE & EXPLOSION HAZARD DATA

Flash Point: N/A	Flammable Limits (in air): LEL: N/A UEL: N/A
Extinguishing Media: Dry chemical, foam	Fire Fighting Procedures: Use self-contained breathing apparatus and protective clothing.
Hazardous Decomposition Products: Carbon dioxide, carbon monoxide, oxides of nitrogen	Special Fire & Explosion Hazards: The release paper will continue to burn even when the original source of combustion is removed.
Method Used: N/A	Auto-Ignition Temperature: 600 - 770° F


SECTION- 5 HEALTH HAZARD DATA

Permissible Exposure Limit: N/A	Signs and Symptoms of Exposure: Will not normally occur.
Effects of Overexposure: Not Hazardous	
Acute: N/A	Carcinogenicity: IARC, NTP, and OSHA do not list this product as a carcinogen.
Chronic: N/A	
Emergency & First Aid Procedures: Eye Contact: Irrigate with water for 15 minutes. Remove contact lenses, if worn. Consult medical personnel if irritation persists. Skin Contact: Not normally hazardous. If contact is made at elevated temperatures treat as thermal burn. Minimize direct contact during handling particularly at high ambient temperatures as the adhesive can be aggressive Inhalation: Noxious fumes can be emitted from the release liner if heated to its melting point. If inhaled at elevated temperatures, remove to fresh air. Seek medical assistance. Ingestion: Induce vomiting. Consult a Physician Primary Route of Entry: None	

SECTION 6 – REACTIVITY DATA



Water Tight Technologies, LLC
 P.O. Box 899, Payson, AZ 85547



Stability: Stable	Incompatibility: Avoid contact of adhesive with strong oxidizing agents.
Hazardous Decomposition Products: In the event of a partial combustion carbon dioxide, carbon monoxide, methane, propane, aldehydes and other organic vapors.	Hazardous Polymerization: Will not occur
Conditions to Avoid: N/A	

SECTION 7 - SPILL OR LEAK PROCEDURES


Steps to be taken in case material is released or spilled: Small spill: N/A
Large Spill: N/A
Waste Disposal Method: Dispose of in accordance with federal, state and local health and pollution laws and regulations in landfill or by incineration.

SECTION 8 – SPECIAL PROTECTION

Respiratory Protection: N/A	Eye Protection: Safety glasses with side shields recommended.
Protective Gloves: Recommended	Other Protective Equipment: When handling this material wear long sleeve shirts, long pants and safety shoes. Washing of hands is recommended after handling coated sheets.
Ventilation: No respirator needed.	



Water Tight Technologies, LLC
 P.O. Box 899, Payson, AZ 85547



SECTION 9 – SPECIAL PRECAUTIONS OR OTHER COMMENTS

Storage/Handling:
Store in cool, dry, well ventilated facility away from flames and oxidizers.

Other Precautions:
Store material in original shipping packaging.

Work/Hygienic Practices:
Maintain good personal hygiene practices.

SECTION 10 - TRANSPORTATION

Regulatory Agency:
Not Regulated. All components are included in the EPA Toxic Substance Control Act (TSCA) Chemical Substance Inventory

Identification Number:
Not Applicable

Proper Shipping Name:
Not Applicable

Labels Required:
Not Applicable

Hazard Classification:
EPA SARA Title III hazard class (40CFR370): None
EPA SARA Title III Section 313 (40CFR372): None
EPA SARA Title III (40CFR355): There are no components present in this product at a level which would require reporting.

Other Requirements:
Not Applicable

SECTION 11 – MISCELLANEOUS INFORMATION

Additional Comments:
None

Date of Previous MSDS:
N/A

Changes Since Previous MSDS:
N/A

Telephone Number for Additional Information:
(888) 269-2122

DISCLAIMER

The information contained herein is based on data considered accurate which has been obtained from other companies and organizations. However, no warranty or representation is expressed or implied that the information is accurate, complete, or representative. Water Tight Technologies, LLC assumes no responsibility for injury to the buyer, the buyer's employees, or any third persons if reasonable safety procedures are not followed.