




Water Tight Technologies, LLC
 P.O. Box 899, Payson, AZ 85547



SECTION 1 – PRODUCT IDENTIFICATION

Product Name: TPO Seam Tape	Manufacturer's Name: Water Tight Technologies, LLC
Item Number(s): TST3100; TST3025	Manufacturer's Address: P.O. Box 899, Payson, AZ 85547
24 Hour Emergency Telephone Number: CHEMTREC – United States 800-424-9300 ; International 202-483-7616 (collect)	NFPA Acute Hazard Rating: Health 0, Flammability 0, Reactivity 0 HMIS Acute Hazard Rating: Health 0, Flammability 0, Reactivity 0
Chemical Name/Synonyms: N/A	Chemical Family: Mixture

SECTION 2 – CHEMICAL COMPOSITION

Ingredient Components (chemical names) Hazardous Components 1% or greater; Carcinogens 0.1% or greater:	% wt or %vol	Case No.	% wt or % vol	OSHA STEL	OSHA PEL ACGIH	ACGIH TLV
Non-Hazardous Ingredients	100					
Total	100					


There are no recognized hazards associated with normal use of this product.

SECTION 3 – PHYSICAL & CHEMICAL CHARACTERISTICS

Appearance/Odor: Tacky white solid with no odor.	Physical State: Solid	Solubility in Water: Insoluble
Boiling Point: N/A	Specific Gravity (HO=1) 0.97	Melting Point: N/A
Vapor Pressure: N/A	Vapor Density (Air=1) N/A	Freezing Point: N/A
Percent Volatiles: N/A	Evaporation Rate: N/A	Reactivity in Water: None



Water Tight Technologies, LLC
 P.O. Box 899, Payson, AZ 85547



SECTION 4- FIRE & EXPLOSION HAZARD DATA


Flash Point: >200°C	Flammable Limits (in air): LEL: N/A UEL: N/A
Extinguishing Media: Foam, water, dry chemical and CO² can also be used.	Fire Fighting Procedures: Treat as Class B fire. Limit fire fighting to those trained to do so. Minimize breathing gases, vapor, fumes or decomposition products. Use supplied-air breathing equipment for enclosed or confined spaces or as otherwise needed.
Hazardous Decomposition Products: In the event of combustion, carbon dioxide, smoke, carbon compound and other decomposition products may be released.	Special Fire & Explosion Hazards: None
Method Used: Estimate based on flash point of most volatile component.	Auto-Ignition Temperature: N/A

SECTION- 5 HEALTH HAZARD DATA

Permissible Exposure Limit: NA	Signs and Symptoms of Exposure: Under normal conditions of use, this product will not release or otherwise result in exposure to hazardous chemicals.
Effects of Overexposure: Toxic fumes may be released during fire. Exposure to fumes may aggravate pre-existing eye, lung, and skin conditions.	
Acute: Irritation, redness.	Carcinogenicity: IARC, NTP, and OSHA do not list this product as a carcinogen.
Chronic: N/A	
Emergency & First Aid Procedures: Eye Contact: Can cause irritation, redness, tearing, blurred vision. Skin Contact: Not normally hazardous Inhalation: Not normally hazardous unless at elevated temperatures. Remove to fresh air. Ingestion: Consult a Physician Primary Route of Entry: None	



Water Tight Technologies, LLC
 P.O. Box 899, Payson, AZ 85547



SECTION 6 – REACTIVITY DATA

Stability: Stable	Incompatibility: None known
Hazardous Decomposition Products: In the event of a partial combustion, fumes, smoke, carbon compounds and other decomposition products may be released.	Hazardous Polymerization: Will not occur
Conditions to Avoid: Exposure to temperatures in excess of 130° F.	

SECTION 7 - SPILL OR LEAK PROCEDURES


Steps to be taken in case material is released or spilled: Small spill: Scoop or shovel material into sealed containers.
Large Spill: Same as small spill.
Waste Disposal Method: If this product becomes a waste, it is considered a non-hazardous waste as defined by RCRA 40CFR261. Dispose of in accordance with local, state, and federal regulations.

SECTION 8 – SPECIAL PROTECTION

Respiratory Protection: N/A	Eye Protection: Safety glasses with side shields recommended.
Protective Gloves: Not Required	Other Protective Equipment: None required under normal installation conditions.
Ventilation: No respirator needed.	



Water Tight Technologies, LLC
 P.O. Box 899, Payson, AZ 85547



SECTION 9 – SPECIAL PRECAUTIONS OR OTHER COMMENTS

Storage/Handling:

Store in cool, dry, well ventilated facility with temperatures not to exceed 130° F.

Other Precautions:

Store material in original shipping packaging.

Work/Hygenic Practices:

Maintain good personal hygiene practices. Product is easily removed with waterless havd cleaner followed by washing with soap and water.

SECTION 10 - TRANSPORTATION

Regulatory Agency:

Not Regulated. All components are included in the EPA Toxic Substance Control Act (TSCA) Chemical Substance Inventory

Identification Number:

Not Applicable

Proper Shipping Name:

Not Applicable

Labels Required:

Not Applicable

Hazard Classification:

**EPA SARA Title III hazard class (40CFR370): None
 EPA SARA Title III Section 313 (40CFR372): None
 EPA SARA Title III (40CFR355): There are no components present in this product at a level which would require reporting.**

Other Requirements:

Not Applicable

SECTION 11 – MISCELLANEOUS INFORMATION

Additional Comments:

None

Date of Previous MSDS:

N/A

Changes Since Previous MSDS:

N/A

Telephone Number for Additional Information:

(888) 269-2122

DISCLAIMER

The information contained herein is based on data considered accurate which has been obtained from other companies and organizations. However, no warranty or representation is expressed or implied that the information is accurate, complete, or representative. Water Tight Technologies, LLC assumes no responsibility for injury to the buyer, the buyer's employees, or any third persons if reasonable safety procedures are not followed.