

PRODUCT DATA SHEET
BRITE-n-EZ® LAP CAULK



Water Tight Technologies, LLC
P.O. Box 899, Payson, AZ 85547
www.watertighttech.com

Description: BRITE-n-EZ® White Lap Caulk is a one-part Elastomeric, solvent release type sealant possessing excellent resistance to weathering. This sealant is especially formulated as a tough, weather resistant sealant. This product should not be screed or smoothed after application. This caulk is meant to prevent water infiltration into seams and overlaps prior to the adhesive setting up. Usually 24 – 48 hours, depending on temperature and humidity.

Suggested Uses: BRITE-n-EZ® Lap Caulk is used on exposed edges of white EPDM or TPO seams, edges of EPDM flashings, top of Termination Bar and top of Pipe Boot clamps. Coverage is approximately 25 ft per 10.5 oz tube

Surface Preparation - Surfaces to be sealed must be dry and free from dust, oil, water, and other contaminants using Membrane Cleaner.

Application Instructions – Standard caulk gun is required for use. Once the plastic top is cut you must puncture the tube through plastic top with a screw driver or long screw or nail to begin application. Do not feather or smooth the bead.

Physical Characteristics:

Contents: Naptha VM&P, Titanium

Color: White

Specific Gravity: (at 20°C) 1.04 g/cm²

Flash Point: 18°C / 64°F

VOC Content: < 449 grams/liter DO NOT THIN

Viscosity: > 20.5 cST

% Solids: 83.6%

Packaging: 10.5 oz tubes

Freight Classification: Flammable Solid, UN1325, PG2. NMFC# 170060 Class 60

Recommended Storage: Store in original, unopened container, indoors and out of direct sunlight at temperatures below 80°F. The shelf life is approximately 24 months if stored in original unopened containers stored at room temperatures between 60° and 80°

NOTE: TECHNICAL INFORMATION AND DATA SHOULD BE CONSIDERED REPRESENTATIVE OR TYPICAL ONLY AND SHOULD NOT BE USED FOR SPECIFICATION PURPOSES.