

PRODUCT DATA SHEET
RUBBERALL® TPO CUT
EDGE SEALANT



Water Tight Technologies, LLC
2500 Dewitt Street
Elkhart, IN 46517
www.watertighttech.com

Description: RUBBERALL® Cut Edge Sealant is a high performance, free flowing material used to seal TPO membrane edges when the TPO membrane is cut, and the polyester scrim is exposed. The Cut Edge Sealant prevents moisture from entering and contaminating the membrane scrim.



Physical Properties:

1. Color – Clear
2. Base – Synthetic Rubber
3. Solids – 14%
4. Viscosity - 3500 cps
5. Flash Point – 39° F (4° C)
6. Odor- Aliphatic, Aromatic

Shelf Life - 1 year when stored at temperature no higher than 80°F in unopened containers.

Surface Preparation - Surfaces to be sealed must be dry and free from dust, oil, water, and other contaminants using Membrane Cleaner.

Application Instructions - Apply 1/8" bead with squeeze bottle. Do not feather or smooth bead.

Packaging:

8 - 16oz. bottles per carton (3.8L) gallon

Coverage:

Approximately 225' - 275' (70-85 m) when applied in 1/8" bead.

Precautions:

Cut Edge Sealant is Flammable. Keep away from open flames, sparks or other sources of ignition. Do not smoke while using product.

Do not use in enclosed or unventilated area.

Avoid breathing vapors. Vapors are heavier than air and may migrate to an ignition area far from the application site.

Avoid contact with eyes. Wear safety glasses. If contact with eyes, immediately rinse with clean water for 15 minutes and contact a physician.

Avoid contact with skin. Wash thoroughly with soap and water.

Recommended Storage: Store in original, unopened container, indoors and out of direct sunlight at temperatures below 80°F. The shelf life is approximately 12 months if stored in original unopened containers stored at room temperatures between 60° and 80°

NOTE: TECHNICAL INFORMATION AND DATA SHOULD BE CONSIDERED REPRESENTATIVE OR TYPICAL ONLY AND SHOULD NOT BE USED FOR SPECIFICATION PURPOSES.