



Water Tight Technologies, LLC
2500 Dewitt Street
Elkhart, IN 46517



SECTION 1 - IDENTIFICATION

Trade Name: One Part Pourable sealant
Product Item #: PS
Relevant Uses: Moisture cure sealant
Details of Supplier of SDS:
Water Tight Technologies, LLC
2500 Dewitt Street, Elkhart, IN 46517
888-649-1020

Emergency Telephone Number: CHEMTREC – US: 800-424-9300; International: 703-527-3887

SECTION 2 – HAZARDS IDENTIFICATION

Material Overview

Appearance	liquid
Color	black
Odor	characteristic

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Hazardous classification: Irritant Category 2

GHS Label Elements

Symbol(s)



Signal Word: Warning

Hazard Statement(s)

H315: Causes skin irritation.

H317: May cause allergic skin reaction.

H319: Causes serious eye irritation.

Precautionary Statement(s)

P273: Avoid release into the environment.

P280: Wear protective gloves/protective clothing/eye protection.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P305 + P351 IF IN EYES: Rinse cautiously with water for several minutes.

+ P338: Remove contact lenses, if present and easy to do. Continue rinsing.

P501: Dispose of contents/container in accordance with local regulation.

R-Phrases

R38: Irritating to skin.

R41: Risk serious damage to eyes.

R43: May cause sensitization by skin contact.

S-Phrases

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S39: Wear eye/face protection.

Carcinogenicity: This product contains no ingredient listed as a carcinogen on California Proposition 65 list.



SECTION 7 – HANDLING AND STORAGE

GENERAL PROCEDURES: For professional or industrial use only. Follow label instructions. Keep out of the reach of children. Not for consumption. No smoking. Do not breathe vapors. Avoid contact with body. Turn off all pilot lights, flames, stoves, heaters, electric motors, welding equipment and other sources of ignition. Empty containers must not be washed and re-used for any purpose. Contact lens wearers must wear protective eye wear around chemical vapors and liquid. Wash hands thoroughly after handling. Flammable vapors may cause flash fire or ignite explosively. To prevent build-up of vapors, use adequate natural and/or mechanical ventilation (e.g. open all windows and doors to achieve cross ventilation). Containers may be hazardous when empty. Never use welding or cutting torch on or near container. Do not cut, drill, grind, or expose containers to heat, sparks, static electricity or other source of ignition. Explosion may occur causing injury or death.

HANDLING: Use adequate ventilation and appropriate respiratory protection to avoid breathing vapors when cover is removed. Ground and bond all equipment when handling flammable solvent-borne material.

Storage

Keep container closed when not in use. Store in a dry, well ventilated area, out of the sun and away from ignition sources. Do not remove or deface label. Prevent water or moist air from entering container.

STORAGE TEMPERATURE: 15.5°C (60°F) Minimum to 35°C (95°F)

Incompatible Materials

Strong oxidizing agents, acids, bases

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin Protection

Wear chemical protective clothing & boots to prevent repeated or prolonged skin contact. Wear impervious gloves, if needed, to prevent repeated or prolonged skin contact.

Environmental Exposure controls

No specific controls are needed.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Paste
Color:	Black
Odor:	Mild mint scent
Auto-ignition:	Not applicable
Flammability limit:	Not applicable
Melting point/freezing point:	Not applicable
% Volatile:	1.07%
Physical State:	Water Solubility: Insoluble
Upper explosion limit:	Not applicable
Lower explosion limit:	Not applicable
Vapor Density (air=1):	>1
Density:	11.59 lbs./gal. (calculated)
VOC:	14.9 g/l
Specific Gravity (water=1):	1.39
Vapor Pressure:	<1
Other Information:	No additional information available



SECTION 10 – STABILITY AND REACTIVITY

Chemical stability:	The product is chemically stable
Possibility of hazardous reactions:	Hazardous polymerization does not occur.
Conditions to avoid:	Not known
Hazardous decomposition products:	Thermal decomposition may produce toxic fumes of Carbon Monoxide (CO) and/or Carbon Dioxide (CO ₂)

SECTION 11 – TOXICOLOGICAL INFORMATION

Amino Silane (Refer to sections 2 and 3) toxicity:

Oral: LD50> 2,000 mg/kg. Remark: Very low order of toxicity.

Skin Absorption: LD50> 2,000 mg/kg. Remark: Very low order of toxicity.

Inhalation: LC50 Not acutely Toxic.

Skin Direct Contact: Slight irritation.

Eye Direct Contact: Severe irritation. Remark: Causes corneal injury.

Exposure Limits: Not applicable.

Sensitization: No.

Reproductive Toxicity: No.

Mutagenicity: No.

Teratogenicity: No.

Synergistic Products: None.

SECTION 12 – ECOLOGICAL INFORMATION

No known applicable information.

SECTION 13 – DISPOSAL CONSIDERATIONS

Disposal methods:

Waste from residues:

If this product as supplied becomes a waste, it does not meet the criteria of a hazardous waste as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. This product becomes a firm synthetic rubber when cured. Please allow to cure before disposal.

Uncleaned packagings:

Recommendation: disposal must be made according to official regulations.

SECTION 14 – TRANSPORTATION INFORMATION

Special shipping information: None.

DOT: Not regulated.

TDG: Not regulated.

PIN: Not regulated.



SECTION 15 – REGULATORY INFORMATION

Rotterdam convention (PIC) Annex III: listed (Tributyl tin compounds (impurities) <2ppm)

U.S. Regulatory information

OSHA 29 CFR 1910-1200 - Irritant.

TSCA - All components of this product are listed on TSCA Inventory.

CLRLA Reportable Quantity - Not applicable.

SARA Title III:

Section 302 Extremely Hazardous Substances - None.

Section 304 - Not applicable.

Section 311/312 - Immediate (acute) health hazard.

Section 313 - None.

RCRA - Refer to section 13.

California Proposition 65 Carcinogens: This product does not contain any chemicals known by the State of California to cause cancer.

California Proposition 65 Reproductive Toxins: This product does not contain any chemicals known by the State of California to cause reproductive harm.

Canadian WHMIS Classification - D2B

SECTION 16 – OTHER INFORMATION

HMIG RATING:

Health: 1 Fire: 0 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe* = Chronic hazard

Summary of Changes

Approval Date: July 1, 2026

Supersedes Date: May 15, 2018


Revision Note: Change to supplier contact information

Key/Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH - Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.



Water Tight Technologies, LLC
2500 Dewitt Street
Elkhart, IN 46517



continued of 5

Disclaimer:

The information herein is presented in good faith and believed to be correct as of the date hereof. Information is based upon supplier-issued safety data sheets and may be subject to error. If apprised of changes, updated SDS will be promptly issued. Users must make their determination regarding the suitability of the product for their own purposes prior to use. In no event will Water Tight Technologies, LLC be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.